(51) International Patent Classification 6 :	A1	(11) International Publication Number: **WO 97/00594**
H04S 1/00, 5/00		(43) International Publication Date: 3 January 1997 (03.01.97)

(54) Title: METHOD AND APPARATUS FOR SPATIALLY ENHANCING STEREO AND MONOPHONIC SIGNALS

(57) Abstract

   A method and apparatus is disclosed which spatially enhances stereo signals without sacrificing compatibility with monophonic receivers. In accordance with one embodiment of the present invention, a stereo enhancement system (60b) is implemented using only two op-amps (51, 52) and two capacitors (C_1 and C_2) and may be switched between a spatial enhancement mode and a bypass mode. In other embodiments, simplified stereo enhancement systems are realized by constructing one of the output channels as the sum of the other output channel and the input channels. In other embodiments, a pseudo-stereo signal is synthesized and spatially enhanced according to stereo speaker crosstalk cancellation principles. In yet other embodiments, the respective spatial enhancements of monophonic signals and stereo signals are integrally combined into a single system capable of blending, in a continuous manner, the enhancement effects of both.

METHOD AND APPARATUS FOR SPATIALLY ENHANCING STEREO AND MONOPHONIC SIGNALS

5

BACKGROUND OF THE INVENTION

1.   Field of the Invention

The present invention relates generally to acoustic signals and

10   particularly to a method and system for enhancing monophonic and stereophonic acoustic signals.

2.   Description of Related Art

It is impossible to achieve the same degree of channel separation in a

15   typical two loud-speaker stereo system that is possible with a pair of headphones. In such a stereo system, acoustic signals arriving at a listener's ear from the left and right loud-speakers which are in phase tend to add, while those which are out of phase tend to cancel one another. This phenomena, known as speaker crosstalk, degrades the perceived spatial and directional

20   qualities of the acoustic image. Further, since speaker crosstalk is a function of the geometry of the interfering wavefronts resulting from the intersection of the left and right acoustic signals, the effects of speakers crosstalk are dependent upon the location of the listener relative to the positions of the left and right speakers. That is, the effects of crosstalk as perceived at one location may be

25   different from those perceived at another location. This positional dependence of crosstalk gives rise to the so-called "dead spots" and "sweet spots" a listener experiences when moving across a listening area.

It is theoretically possible to cancel crosstalk by enhancing the stereo signals as a function of the particular positions of the speakers and the dynamic

30   position of the listener. In practice, however, such cancellation is impossible to achieve since the particular arrangement of a listener's speakers and the dynamic position of the listener cannot be predicted. Numerous stereo enhancement systems have been disclosed recently which attempt to compensate

for this positional dependence of crosstalk by enhancing the (L-R), or difference, component and the (L+R), or sum, component of the stereo signals. Such systems, however, are relatively complex and expensive to implement.

Further, many of the conventional stereo enhancement systems fail to effectively address the monophonic aspects of stereo signals. For instance, it is desirable in a stereo enhancement system to retain compatibility with monophonic receivers, that is, receivers which receive only the modified sum (L+R) component of the stereo signal. Receiving only the modified sum component without the ability to extract the spatial effects encoded into the difference signal results in an undesirable degradation of the original monophonic acoustic image.

In addition, since many of the presently broadcast and recorded acoustic images include both stereo and monophonic sources, it is also desirable for a stereo enhancement system to not only spatially enhance monophonic acoustic images but also to have the ability to smoothly and automatically transition between stereo signal enhancement and monophonic signal enhancement.

SUMMARY

A method and apparatus is disclosed which spatially enhances stereo signals without sacrificing compatibility with monophonic receivers. In accordance with one embodiment of the present invention, a stereo enhancement system is implemented using only two op-amps and two capacitors and may be switched between a spatial enhancement mode and a bypass mode. In other embodiments, simplified stereo enhancement systems are realized by constructing one of the output channels as the sum of the other output channel and the input channels. In other embodiments, a pseudo-stereo signal is synthesized and spatially enhanced according to stereo speaker crosstalk cancellation principles. In yet other embodiments, the respective spatial enhancements of monophonic signals and stereo signals are integrally combined into a single system capable of blending, in a continuous manner, the enhancement effects of both.

-2-

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1a is block diagram illustrating a conventional lattice signal flow topology;

Figure 1b is block diagram illustrating a conventional shuffle signal flow topology;

Figure 2a is a block diagram illustrating a conventional sum-invariant signal flow topology;

Figure 2b is a block diagram illustrating a sum-invariant topology of a stereo enhancement system in accordance with the present invention;

Figures 3a and 3b are block diagrams illustrating other sum-invariant topologies in accordance with the present invention;

Figure 4 is a schematic diagram of a stereo enhancement system in accordance with one embodiment of the present invention;

Figures 5a, 5b, 6, and 7 are schematic diagrams of stereo enhancement systems in accordance with other embodiments of the present invention;

Figures 8a and 8b are block diagrams illustrating conventional pseudo-stereo topologies;

Figures 9a and 9b are block diagrams illustrating pseudo-stereo enhancement topologies in accordance with the present invention;

Figures 10a, 10b, 11a, 11b, 12, 13, and 14 are block diagrams illustrating stereo/mono enhancement topologies in accordance with the present invention;

Figure 15 is a schematic diagram illustrating an all-pass filter utilized in some embodiments of the present invention;

Figures 16-19 are schematic diagrams of stereo/mono enhancement systems in accordance with the present invention; and

Figure 20 is a block diagram of a topology for implementing some of the stereo/mono topologies of the present invention in a digital signal processor.

DETAILED DESCRIPTION OF THE INVENTION

It is to be understood that in the detailed discussion that follows,

components common to the various embodiments and drawing figures are appropriately labelled with the same notations.

Before discussing aspects of the present invention in detail, it is necessary to mention several important underlying principles. First, audio

5   enhancement systems should be channel symmetric in order to preserve the centering of the original stereo signal. That is, the left and right channels of the audio signal should be identically processed such that a reversing of the inputs to the audio enhancement system would not effect the operation of the system.

10   Channel-symmetric audio enhancement systems are typically implemented using either a lattice topology or a shuffle topology. Figure 1a illustrates the signal flow in a lattice topology, where L and R represent the left and right channel input signals respectively, and L' and R' represent the left and right output signals respectively. In such a lattice topology, each of the

15   output signals is a sum of its respective input signal times a linear transfer function S(s) and the opposite input signal times a linear transfer function A(s). That is:

$$L'=S(s)L+A(s)R$$
$$R'=S(s)R+A(s)L$$

20

In order to maintain channel symmetry, the transfer functions S(s) of filters 1 and 4 must be identical, and the transfer functions A(s) of filters 2 and 3 must be identical.

Figure 1b illustrates the signal flow in a shuffle topology, where the
25   output signals L' and R' are determined as follows:

$$L'=P(s)(L+R)+N(s)(L-R)$$
$$R'=P(s)(L+R)-N(s)(L-R)$$

(1)

Hence, a sum of input signals L and R, (L+R), is constructed at summing element 11 and processed through a filter 14 having a transfer function P(s). A difference of input signals L and R, (L-R), is constructed at summing element 10 and processed through a filter 13 having a transfer function N(s). The

5 processed difference signal is inverted at inverter 17 and recombined with the processed sum signal at summing elements 15, 16, to produce output channels L' and R'.

The transfer functions associated with the lattice and shuffle topologies of Figures 1a and 1b, respectively, are related to one another as follows:

10

$$S(s) = P(s) + N(s) \quad \text{and} \quad A(s) = P(s) - N(s)$$

This relationship allows an audio enhancement system implemented in one topology to be easily converted to the other topology.

15 Further, it is desirable for an audio enhancement system to be sum invariant so as to be compatible with monophonic receivers. A sum invariant topology is that which the sum, or (L+R), component of the stereo signal is not altered such that the sum of the left and right input signals L, R equals the sum of the left and right output signals, L', R', as expressed below:

20

$$L' + R' = L + R \tag{2}$$

The lattice topology of Figure 1a is sum-invariant, where the transfer functions S(s) and A(s) are related as follows:

25

$$S(s) + A(s) = 1$$

The shuffle topology of Figure 1b can be made sum-invariant by constraining transfer function P(s) such that:

30

$$P(s) = \frac{1}{2}$$

-5-

Applicant has found that in some instances a sum-invariant topology
such as that shown in Figure 2a may offer a more efficient implementation of a
stereo enhancement system. Referring to Figure 2a, the right signal R is
inverted at inverter 21 and combined with the left input signal L at summing
5   element 20 to produce a difference signal (L-R), which is then processed
through a filter 22 having a transfer function B(s). The processed difference
signal (L-R) is summed with the original left input signal L at summing element
23 to produce the left output signal L'. The processed difference signal (L-R)
is inverted at inverter 24 and summed with the original right input signal R at
10   summing element 25 to produce the right output signal R'. The relationship
between the input signals L, R and output signals L', R' may be expressed as
follows:

$$L'=L+B(s)(L-R)$$
$$R'=R-B(s)(L-R)$$

15   (3)

The transfer function B(s) is related to the transfer function A(s) used in
the lattice topology illustrated in Figure 1a as follows:

$$B(s)=-A(s)$$

20   (4)

Rearranging the sum-invariant relationship expressed in equation (2)
above gives:

$$R'=L+R-L'$$

25   (5)

This relationship has led Applicant to a modified sum-invariant topology, as
illustrated in Figure 2b, where the right output signal R' is constructed by
subtracting the left output signal L' from the sum (L+R) of the input signals.
Thus, the right input signal R is inverted at inverter 31 and summed with the
30   left input signal L at summing element 30. The resultant difference signal (L-
R) is processed by filter 32 having the transfer function B(s) and recombined

with the original left input signal L at summing element 33. The left output
signal L' is inverted at inverter 34 and summed with the original right R and
left L input signals at summing element 35 to produce the right output signal
R'. The advantages resulting from the sum-invariant topology of Figure 2b will

5 be apparent shortly.

It should be noted that where channel symmetry is not a requirement of
the particular enhancement system, as is the case when constructing pseudo-
stereo signals from a monophonic signal, the topologies of Figures 2a and 2b
may be broadened as illustrated in Figures 3a and 3b, respectively. Taking the

10 topology shown in Figure 3a, the left L and right R signals are combined and
processed in function block 40 which may implement either a linear or non-
linear function. This processed signal is added to the left input signal L at
summing element 41 to produce the left output signal L' and subtracted from
the right input signal R via inverter 43 and summing element 42 to produce the

15 right output signal R'. The processing performed by filter 40 may be any
suitable signal shaping function of one or both of the input signals L, R.

Referring to Figure 3b, the processing function of filter 45 may be any
suitable signal shaping function of one or both of the two input signals L, R.
The output signal of filter 45 is provided as the left output signal L', while the

20 right output signal R' is produced by subtracting the left output signal L' from
the sum (L+R) of the input signals.

The shuffle topology (Figure 1a) is generally preferred over the lattice
topology (Figure 1b) since the shuffle topology requires only two filters 13-14,
where the lattice topology requires four filters 1-4. Nevertheless, Applicant has

25 found that the lattice topology allows for a simpler circuit implementation of a
stereo enhancement system.

Figure 4 shows a stereo enhancement system 50 in accordance with one
embodiment of the present invention. Enhancement system 50, the design of
which stems from the lattice topology of Figure 1a, requires only two op-amps

30 51, 52. The left input signal L is provided to the positive input of op-amp 51
and to the negative input of op-amp 52 via resistor R3, while the right input

-7-

signal R is provided to the positive input of op-amp 52 and to the negative input of op-amp 51 via resistor R1. Op-amps 51 and 52, which are configured as a leaky integrator, respectively combine the left L and right R input signals as follows:

$$L'=(1+\frac{A_0}{1+s\tau_P})L-\frac{A_0}{1+s\tau_P}R$$

$$R'=(1+\frac{A_0}{1+s\tau_P})R-\frac{A_0}{1+s\tau_P}L$$

where A_0 is the gain of the bass frequency boost and τ_P is the time constant of the transfer function which determines the roll-off frequency of the boost. The values of A_0 and τ_p, which are in the preferred embodiment approximately 3.125 and 600 μs (corresponding to a frequency of 265 Hz), respectively, may be set according to the following:

$$A_0=\frac{R2}{R1}=\frac{R4}{R3} \quad \text{and} \quad \tau_p=R2\cdot C1=R4\cdot C2$$

Since the top and bottom halves of enhancement system 50 are symmetric, the values of resistors R1, R2, and capacitor C1 may in some embodiments be equal to the values of R3, R4 and capacitor C2, respectively. The values for the above-mentioned resistors and capacitors may, in actual embodiments, vary depending upon the operating characteristics of the selected op-amp, noise and input impedance considerations, and cost and size restrictions of discrete capacitors C1 and C2, as is well understood in the art. In a preferred embodiment, op-amps 51 and 52 are low noise audio-grade op-amps such as the TL074, available from Texas Instruments.

In contrast to some conventional audio enhancement systems, enhancement system 50 of Figure 4 does not boost or otherwise alter the high-frequency portions of the difference (L-R) signal, i.e., those portions above approximately 1100 Hz. As a result, the embodiment of Figure 4 achieves a

superior balance between centered and off-centered acoustic images in the source signal than do those conventional systems which provide more power to the high-frequencies of the difference (L-R) signal. It should also be noted that the embodiment of Figure 4 does not alter the sum (L+R) signal, thereby

5   preserving monophonic acoustic images and retaining compatibility with monophonic receivers. Although contrary to numerous prior teachings of crosstalk cancellation which suggest modifying the sum component, Applicant feels that the relatively small acoustic advantages realized from modifying the sum signal are outweighed by the benefits of sum-invariance, i.e., retaining

10 monophonic compatibility.

The operation of enhancement system 50 of Figure 4 may be also be described in terms of the shuffle topology of Figure 1b and the sum-invariant based topologies of Figures 2a, 2b. In the case of a shuffle topology, the transfer functions N(s) and P(s) are of the form:

15

$$N(s)=0.5\frac{N_0+s\tau_P}{1+s\tau_P} \quad \text{and} \quad P(s)=0.5$$

20 where N_0 is the gain of the bass frequency boost and τ_P is the time constant which determines the roll-off frequency of the boost. In the preferred embodiment, the corresponding values of N_0 and τ_p should be approximately 7.25 and a τ_P of about 600 μs, respectively. Setting P(s) equal to one-half ensures sum-invariance, as described above.

25 The virtual short between the inputs of op-amps 51 and 52 allows the negative inputs of respective op-amps 51 and 52 to connected together via a resistor R11, as shown in Figure 5a, thereby resulting in the elimination of one resistor. Enhancement system 60a of Figure 5a operates in a manner similar to that of Figure 4 and, accordingly, those components common to the

30 embodiments of Figures 4 and 5a are similarly labelled. The simpler design of enhancement system 60a also allows the left and right input signals to be

directly coupled to the positive inputs of op-amps 51 and 52, respectively. As
a result, enhancement system 60a desirably exhibits a high input impedance.
Resistors R2 and R4 must be equal and capacitors C1 and C2 must be equal.
The values of A_0 and τ_P are determined as follows:

5

$$A_0 = \frac{R2}{R11} \quad \text{and} \quad \tau_P = R2 \cdot C1$$

Note that parameters A_0 and τ_P may easily be adjusted by varying the resistance
of resistor R11 which, in some embodiments, is a potentiometer.

10   In yet another embodiment, a switch SW1 may be added in series with
resistor R11 as shown in Figure 5b. The resultant enhancement system 60b
may thus switch between an enhancement mode, in which the left and right
input signals L, R are enhanced as described above to produce enhanced left
and right output signals L', R', and a bypass mode, in which the left and right
15   input signals L, R pass unmodified through enhancement system 60 and appear
as left and right output signals L', R'. Switch SW1 may be any suitable
switching device. The low-pass filter nature of op-amps 51 and 52 desirably
prevents instantaneous voltage changes between input signals and output signals.
Thus, when switching between modes, the left and right output signals L', R'
20   will exponentially converge to their respective input signals L, R as a function
of the time constant τ_p, thereby resulting in smooth switching transitions
between modes. Accordingly, complex switching techniques which minimize
switching noise, such as zero-crossing switching techniques, are unnecessary.
           As mentioned earlier, the sum-invariant topologies depicted in Figures
25   2a and 2b may allow for an improved circuit implementation of stereo
enhancement system in accordance with the present invention. Referring to
Figure 6, the design of enhancement system 70 is based upon the sum-invariant
topology illustrated in Figure 2b. The left output signal L' is produced through
op-amp 71 and its associated feedback elements R21 and C20, which operate as
30   a leaky integrator, from the sum of the left and right input signals (L+R). The
right output signal R' is constructed according to equation (5), i.e., op-amp 72

sums the left output signal L' with the input signal sum (L+R) to produce the right output signal R'. In order to ensure proper summing at op-amp 72, resistors R23 and R24 should be of equal value, and resistors R22 and R25 should be of equal value. Note that the sum-invariant design of enhancement

5   system 70 requires only one capacitor C20, as opposed to the two capacitors required in the embodiments of Figures 4 and 5. Switch SW2 allows the enhancement system 70 to switch between enhancement and bypass modes as previously described with respect to Figure 5.

Enhancement system 70 operates according to the aforementioned B(s)
10   transfer function,

$$B(s) = \frac{B_0}{1 + s\tau_P}$$

(7)

where

15

$$B_0 = 0.5(N_0 - 1)$$

(8)

The B_0 and τ_p parameters are determined as follows:

20

$$B_0 = \frac{R21}{R20} \quad \text{and} \quad \tau_p = R21 \cdot C20$$

Preferably, the values of B_0 and τ_p are approximately 3.125 and 600μs, respectively. With the exception of the above mentioned constraints, the values

25   of the resistors contained in enhancement system 70 may vary depending upon desired operating characteristics. Note that since capacitor C20 prevents the voltage at the negative input of op-amp 71 from changing instantaneously, voltage continuity of the left output signal L' is preserved when switching between modes via switch SW2. Thus, when enhancement system 70 is

30   switched from enhancement to bypass mode, op-amp 71 acts as a voltage follower, with the output voltage offset by the voltage across C20. Capacitor

C20 will gradually discharge through the parallel combination of resistors R20 and R21. When switch SW2 switches from bypass to enhancement mode, capacitor C20 is exponentially charged, thereby preserving the voltage continuity of the output and minimizing switching impulse energy. Resistors

5 R20, R21 and capacitor C20 determine the time constant of exponential transients caused when switching between modes. Line 74 serves primarily as a shunt to prevent parasitic coupling between lines 73 and 75 from producing any unwanted residual effect in bypass mode. Where not necessary, line 74 may be removed such that capacitor C20 discharges only through R21.

10   The embodiments described above with reference to Figures 4-6 employ a minimum number of op-amps in order to minimize implementation cost. The distortion and fidelity associated with enhancement system 70 may be improved by modifying enhancement system 70 to employ op-amps which operate only in an inverting mode. Such a modification is illustrated in Figure 7 as stereo

15 enhancement system 80. Op-amp 81 and resistors R30, R31 invert the left input signal L, and op-amp 83 and resistors R38, R39 invert the R input signal, where R30 = R31 and R38 = R39. Op amp 84 and associated resistors R40-R43 produce the right output signal R' according to the sum-invariant constraint of Equation (5). Resistors R40-R43 should be of equal value to ensure proper

20 summing at op-amp 84. Op-amp 82 and associated capacitor C30 and resistors R32-R37 produce the left output signal L' according to Equations (3) and (7), where the B_0 and τ_p parameters, which are preferably 3.125 and 600 μs, respectively, govern the selection of other component values as follows:

25
$$8\tau_p B_0 = R37 \cdot C30$$

$$R32 = R33 = \frac{R37}{2B_0}$$

$$R36 = \frac{R37}{4B_0}$$

30
$$R35 = R37$$

As stated earlier with reference to other embodiments, the precise values of the components employed in enhancement system 80 may vary depending upon desired operating characteristics. Resistors R32, R33 and R36 are related radiometrically to R37. Switch SW3 switches enhancement system 80 between
5   enhancement and bypass modes. When SW3 connects lines 85 and 86, enhancement system 80 enters enhancement mode and operates as described above. When switch SW3 connects line 85 to ground via resistor R34, enhancement system 80 enters bypass mode. In this mode, op-amp 82 operates as an inverter and provides a left output signal L' equal to the left input signal
10 L. It follows, then, that the L' signal and inverted L signal cancel at op-amp 84 such that the right output signal R' is equal to the right input signal R. Capacitor C30 helps to ensure voltage continuity between modes as discussed previously. When switching from enhancement to bypass mode, C30 completely discharges to ground through the parallel combination of resistors
15 R36 and R34. While not necessary to the operation of system 80, the path to ground through resistor R34 helps to eliminate parasitic coupling. When switching from bypass to spatialization mode, C30 gradually charges in the normal course of operation.

The embodiments described above with reference to Figures 4-7 are
20 advantageous over prior enhancement systems based upon the shuffle topology in that the voltages of the internal nodes of the embodiments of Figures 4-7 will not exceed the maximum input voltage or maximum output voltage. Conversely, in shuffle topology based enhancement systems, the internally generated sum (L+R) and difference (L-R) signal voltages may be twice that of
25 the maximum input signals, thereby requiring either (1) halving the voltage range of the input signals or (2) dividing the sum (L+R) and difference (L-R) signals by a factor of two. The former alternative undesirably limits the range of compatible input signal levels, while the latter alternative undesirably reduces the signal to noise ratio (by as much as 6 dB).

30 The above described embodiments can easily be implemented with a digital signal processor. The pole and zero frequencies used in the above

-13-

transfer functions are a small fraction of typical audio sample rates. Thus, the bilinear transformation can be used to derive a discrete time version. As is well understood in the art of digital signal processing, the bilinear transformation is a useful approximation which relates the s-plane of the Laplace transform to the discrete-time z-plane as follows:

$$s = \frac{2}{T} \frac{1 - z^{-1}}{1 + z^{-1}}$$

where T is the reciprocal of the signal sampling rate. As an example, this can be applied to the B(s) transfer function used in the sum-invariant topologies as follows:

$$B(z) = \frac{B_0}{1 + \frac{2}{T}\tau_P} \frac{1 + z^{-1}}{1 + \frac{1 - \frac{2}{T}\tau_P}{1 + \frac{2}{T}\tau_P} z^{-1}}$$

Using a sample rate of 44.1 kHz and the parameter values disclosed above, the above expression reduces as follows:

$$B(z) = 0.057956 \frac{1 + z^{-1}}{1 - 0.962908 z^{-1}}$$

An efficient approach to computing a spatially enhanced data sample can be obtained by using the signal flow illustrated in the topology of Figure 2a in conjunction with the above-denoted B(z). It is to be understood that a particular topology which yields the greatest efficiency in an analog implementation does not necessarily yield the most efficient digital implementation. For instance, in analog implementations, the number of inverting and summing operations significantly affects implementation cost,

-14-

while the number of signals added or inverted in a particular operation has only a slight impact upon implementation cost. In a digital implementation, on the other hand, the total number of summing operations is a function of the total number of signals so summed minus the number of summing operations.

5   Further, negations typically impose no additional overhead. As a result, the sum-invariant topology of Figure 2a is probably preferable over that of Figure 2b for the digital implementation of stereo enhancement systems in accordance with the present invention. It should be further noted that the most economical DSP implementation may depend upon the architecture of the particular digital

10   signal processor used. Nonetheless, a sum-invariant based DSP implementation will usually be superior to those based upon either the lattice or shuffle topologies. It is to be understood, however, that circuit designs based upon each of the above described topologies can be easily mapped from the analog domain to the discrete-time digital domain.

15   In accordance with other embodiments of the present invention, a system is disclosed which spatially enhances not only stereo signals but also monophonic signals in a manner similar to those previously described. A complete understanding of these other embodiments requires an appreciation of some basic principles used in the conversion of monophonic signals to pseudo-

20   stereo signals.

         It is well understood that a pseudo-stereo signal may be synthesized from a monophonic signal (e.g., a signal in which the right and left channels are identical) by spatially "placing" the sound towards either the left or right channel in a selective manner dependent upon the frequency of the monophonic

25   input signal. Such a synthesis may be accomplished by first modifying the input signal and then adding and subtracting this modified signal to and from, respectively, the original input signal to produce left and right channels which are different.

         For instance, Figures 8a and 8b illustrate two common topologies for

30   such synthesis. Referring first to Figure 8a, the monophonic input signal M is routed through an all-pass filter 90 having a transfer function C(s). The output

-15-

of filter 90 is alternately added to, via summing element 92, and subtracted from, via inverter 91 and summing element 93, attenuated replicas of the original input signal M to produce left L' and right R' pseudo stereo signals, respectively. The relationship between output signals L', R' and the input

5   signal M may be expressed as follows:

$$L'=M(0.5+C(s))$$
$$R'=M(0.5-C(s))$$

where C(s) is an all-pass transfer function of the following form:

10

$$C(s)=C_0\frac{(1-s\tau_1{}^*)(1-s\tau_2{}^*)}{(1+s\tau_1)(1+s\tau_2)}\cdots\frac{(1-s\tau_n{}^*)}{(1+s\tau_n)}$$

Typically, the time constants $\tau_1\text{-}\tau_n$ will, in actual implementations, naturally occur in complex conjugate pairs. The constant C_0 determines the

15   "depth" of the pseudo-stereo effect. This effect is maximized when C_0 is equal to either 0.5 or -0.5. At these values of C_0, certain frequencies will appear exclusively in one of the output channels. The sign of C_0 is somewhat arbitrary, since reversing the sign is merely equivalent to swapping the L' and R' channel outputs of Figure 8a. The number of crossover points, that is, the

20   number of particular frequencies at which the energies in the left and right channels are equal, is determined by the order of C(s). Note that the gain element 94 of Figure 8a is not essential, but rather has been included to aid in understanding embodiments of the present invention which later follow. This also allows the Figure 8a topology to meet the following criterion:

25

$$L'+R'=M$$

which implies that the topology will be sum-invariant if the M input signal is constructed by summing left L and right R input signals.

30   The topology illustrated in Figure 8b, which operates in a manner identical to that of the topology of Figure 8a, may provide a more economical

implementation in certain cases.

The pseudo-stereo topologies illustrated in Figures 8a and 8b suffer from a couple of drawbacks. If C_0 is chosen to achieve maximum depth, i.e., equal to either 0.5 or -0.5, the contrast between left and right channels may be too

5   extreme and lead to a "deaf-in-one-ear" phenomenon. This undesirable effect may be minimized by increasing the order of the all-pass filter transfer function $C(s)$. Such a remedy, however, results in an increased implementation cost. This deaf-in-one-ear phenomenon may minimized by simply reducing the value of C_0 in order to provide a more acoustically plausible spread of the input

10   signal. Reducing C_0, however, will cause a decrease in the phase difference between the left and right channels and, therefore, will diminish the perceived spaciousness of the acoustic image. In other words, reducing C_0 undesirably allows speaker crosstalk to cancel out-of-phase energy in the bass frequencies.

In accordance with the present invention, Applicant has found that the

15   deaf-in-one-ear phenomenon may be minimized, without significantly diminishing spaciousness, in one of two ways. In the first approach, a modified $C(s)$ transfer function may be implemented, where $C(s)$ is re-defined as:

20
$$C'(s) = C_0 \frac{(1-s\tau_z)(1-s\tau_1{}^*)(1-s\tau_2{}^*)}{(1+s\tau_p)(1+s\tau_1)(1+s\tau_2)} \cdots \frac{(1-s\tau_n{}^*)}{(1+s\tau_n)}$$

such that

25
$$|C_0| \frac{\tau_z}{\tau_p} > \frac{1}{2} \quad \text{and} \quad \tau_p > \tau_z$$

where τ_p and τ_z are real, positive and lie in the same bass frequency range as does the τ_p used in the earlier described stereo enhancement systems. The modified transfer function $C'(s)$ exhibits a bass frequency boost and, by

30   dominating the output, allows a greater separation between channels for bass frequencies than for higher frequencies. While achieving satisfactory results,

such an approach undesirably results in a large power level discrepancy between the monophonic input signal M and the pseudo-stereo output signals L', R'. It is to be noted that prescaling the monophonic input signal M does not provide an effective solution for reasons that will later become apparent.

5   In the second and preferred approach, one of the pseudo-stereo synthesis topologies illustrated in Figures 8a and 8b may be cascaded with the stereo enhancement systems described above in accordance with the present invention, as illustrated in Figure 9a. In this stereo/mono enhancement topology, filter 100 creates the pseudo-stereo left channel on line 103 while inverter 101 and

10   summing element 102 create the pseudo-stereo right channel on line 104. A stereo enhancement system -107 enhances these pseudo-stereo channel signals to produce left and right output signal L', R' on lines 105 and 106, respectively. System 107 may be any suitable one of the stereo enhancement systems previously described in accordance with the present invention. Note that since

15   each of previously described embodiments of stereo enhancement systems are channel-symmetric, the particular channel assignment to system 107 is arbitrary. It is to be understood that although the pseudo-stereo portion of the topology of Figure 9a is based upon the topology of Figure 8b, it may in other embodiments be based upon the topology of Figure 8a.

20   Using the sum-invariant relationship R' = L + R - L', the stereo/mono enhancement topology of Figure 9a may be simplified to that of Figure 9b, where transfer function D(s) represents the enhancement function performed by system 107 in the topology of Figure 9a. The outputs L' and R' are related to input M as follows:

25

$$L'=M(0.5+C(s)D(s))$$
$$R'=M(0.5-C(s)D(s))$$

          D(s) is defined as follows:

30

$$D(s) = \frac{D_0 + s\tau_P}{1 + s\tau_P}$$

(9)

where D_0 is the DC gain of D(s). The D(s) transfer function may be related to the B(s) transfer function utilized in previous embodiments as follows:

$$D(s) = 1 + 2B(s)$$

and thus

$$D_0 = 1 + 2B_0$$

It follows that the monophonic input signal M is related to the left L' and right R' output signals as follows:

$$L' = M(0.5 + C(s)(1 + 2B(s)))$$
$$R' = M(0.5 - C(s)(1 + 2B(s)))$$

Since the pseudo-stereo (L-R) difference signal tends to be more sensitive to excessive bass frequency boost than does a typical stereophonic (L-R) difference signal, the boost associated with a pseudo-stereo enhancement system should be somewhat lower than that of a pure stereo enhancement system such as those described earlier. Applicant has chosen D_0 to be equal to just over half of $2B_0 + 1$, i.e., approximately 4.5. The time constant τ_p is, as mentioned previously, approximately equal to 600 μs. The particular order of transfer function C(s) involves a tradeoff between superior sound quality (higher order) and implementation cost (lower order). In a preferred embodiment to be described shortly, C(s) is implemented in a manner so as to have three poles and zeroes, an order which Applicant believes achieves a satisfactory compromise between sound enhancement and implementation cost. The preferred time constants for the three poles and zeroes are 46μs, 67μs and 254μs, respectively, which are all real. Applicant has found that a value of 0.2 for the constant C_0 results in an optimal tradeoff between deep separation and

-19-

shallow subtlety.

In typical audio applications, the nature of the received signal (i.e., whether stereophonic or monophonic) is usually not known. In some instances, such as FM radio transmissions, the received signal may vary between a

5   stereophonic and monophonic nature. Thus, it would be desirable to provide a mechanism capable of not only enhancing both the stereo and mono signals but also of smoothly switching between such modes. In accordance with the present invention, a pseudo-stereo synthesis system 131 may be cascaded with stereo enhancement system 126 as illustrated the topology in Figure 10a. It is

10   to be understood that stereo enhancement system 126 may be any of the previously described stereo enhancement systems. Where the input signal is of a monophonic nature, e.g., where the left input signal L is identical to the right input signal R, the topology of Figure 10a will operate in a manner identical to that of the topology of Figure 9a. The gain of a variable gain element 121 may

15   be varied between zero and unity in response to an external control signal (not shown) such as a stereo blend signal received from an FM stereo decoder or a stereophonic source detection circuit or even a user control. When gain element 121 is set to have a gain of zero, the pseudo-stereo synthesis portion 131 is effectively disabled such that the operation of the topology of Figure 10a

20   is determined solely by stereo enhancement system 126. Thus, variable gain element 121 allows for the dynamic control of the depth of the pseudo-stereo synthesis effect. Note that it is possible, with the appropriate choice of parameters, to fix the gain of variable gain element 121 at unity for all signal sources.

25   In practice, most stereo sources contain sufficient out-of-phase channel information to effectively mask the pseudo-stereo effect, while any monophonic components present will benefit from the pseudo-stereo effect. Thus, if a stereo signal contains very little spatialized information, i.e., a minimal difference (L-R) signal, the pseudo-stereo component will dominate the stereo component.

30   Thus, for such a stereo signal, the pseudo-stereo effect will spatially enhance the corresponding acoustic image. Where variable gain element 121 has unity

gain, the inputs and outputs of the topology of Figure 10a may be related to one another as follows:

$$L'=L+B(s)(L-R)+C(s)(1+2B(s))(L+R)$$
$$R'=R-B(s)(L-R)-C(s)(1+2B(s))(L+R)$$

(10)

If variable gain element 121 is used to dynamically switch between modes, i.e., between enabling and disabling pseudo-stereo synthesis portion 131, certain measures will need to be taken to ensure low switching noise. For instance, the gain of variable gain element 121 should varied at such a rate so as not to introduce significant high-frequency energy into the acoustic signals.

In the topology of Figure 10a, both pseudo-stereo input signals (synthesized from a monophonic input signal via portion 131) and stereophonic input signals are filtered via stereo enhancement system 126 and, thus, are processed according to the same previously disclosed parameters associated with the transfer function B(s). Since, however, pseudo-stereo signals generated from monophonic signals are different from pure stereophonic signals, it would be advantageous for each of such signals to be spatially enhanced according to different parameters while simultaneously enabling a blending of the two enhancement effects.

Thus, in accordance with another embodiment of the present invention, a pseudo-stereo synthesis system 140 is cascaded to the output lines 143, 144 of stereo enhancement system 126 as illustrated in the topology of Figure 10b. In this topology, the stereo enhancement parameters and thus the spatially enhancing effect of stereo enhancement circuit 126 will affect only stereophonic signals received on input lines 141, 142 (since monophonic signals do not contain a (L-R) difference component, monophonic input signals received on lines 141, 142 pass unmodified through stereo enhancement system 126). These unmodified monophonic input signals are processed in pseudo-stereo synthesis system 140 by a filter 147 having a transfer function of C(s)D(s), where C(s) and D(s) synthesize and spatially enhance, respectively, the pseudo-stereo signal. The topology of Figure 10b operates, in all other respects, in a

-21-

manner identical to that of the topology of Figure 10a. Where variable gain
element is set to unity gain, the inputs and outputs of the topology of Figure
10b may be related to one another as follows:

$$L'=L+B(s)(L-R)+C(s)D(s)(L+R)$$
$$R'=R-B(s)(L-R)-C(s)D(s)(L+R)$$

(11)

In a preferred implementation, D(s) is of the form disclosed in Equation
(9), where D_0 and τ_p are approximately 4.5 and 600 μs, respectively.

The topologies of Figures 10a and 10b may be modified so as to operate
according to shuffle-style topologies as illustrated in Figures 11a and 11b,
respectively. The topology of Figure 11a uses the same enhancement filter
167, having a transfer function of N(s), in processing both stereo and pseudo-
stereo signals. That is, like the topology of Figure 10a, the topology of Figure
11a uses the same parameters in spatially enhancing both stereo and pseudo-
stereo signals. The function N(s) is of the form previously described with
respect to Figure 1b. Pseudo-stereo filter 164 operates according to the
previously described transfer function C(s) multiplied by a factor of 2.
Assuming that Equation (8) remains valid, the relationship between the inputs
and outputs of the topology of Figure 11a may be expressed according to
Equation (10). In a manner similar to the topologies of Figures 10a and 10b,
variable gain element 121 may be either manually or automatically controlled to
accommodate a variety of types of input signals, or set to unity gain and still
handle most monophonic and stereo input signals.

The topology of Figure 11b, a modified version of the topology of
Figure 11a, utilizes distinct spatial enhancement parameters for stereo and
pseudo-stereo signals in a manner similar to that described with respect to the
topology of Figure 10b. In the topology of Figure 11b, unlike that of Figure
11a, the pseudo-stereo signal is synthesized and spatially enhanced by filter 147
according to transfer functions C(s) and D(s), respectively, and summed with
the enhanced stereo signal generated by filter 167 according to transfer function
N(s). Again, transfer functions C(s), D(s), and N(s) are of the respective forms

-22-

previously described.

Note that these topologies are advantageously sum-invariant notwithstanding the asymmetrical nature of pseudo-stereo transfer function C(s). It should also be noted that since monophonic input signals do not contain a (L-

5   R) difference component, when such a monophonic signal is provided as an input to the topologies of Figures 11a and 11b, the (L-R) difference signal path (created by summing element 160) will contain no signal. Thus, the coupling of the (L+R) sum signal to the difference signal path via filter 164 and summing element 166 is vital in the construction of the left output signal L'.

10 Since the above topologies are sum-invariant, they may be modified to operate according to the sum-invariant topologies of Figures 3a and 3b, thereby resulting in more simplified and more cost-effective implementations. Further, Applicant has found that greater simplification may be achieved by setting the pole time constant of the D(s) transfer function equal to that of the B(s) transfer

15 function. In this manner, the D(s) transfer function need not be explicitly implemented while advantageously providing distinct enhancement parameters for stereo and pseudo-stereo signals. Thus, the filter which would have otherwise implemented C(s)D(s) now need only implement C(s), thereby allowing for the elimination of one pole-determining capacitor. Note that this

20 simplification results in the elimination of one delay element in digital implementations.

The resultant simplified topologies derived from the topologies of Figures 11a and 11b are illustrated in Figures 12 and 13, respectively. In the topology of Figure 12, summing elements 208 and 209, along with inverter

25 210, replicate the style of the sum-invariant topology of Figure 3a. Summing element 200, variable gain element 210, filter 202 having a transfer function C(s), and gain element 205, construct the pseudo-stereo signal. The magnitude of the signal output from filter 202 will, to a significant degree, determine the magnitude of the pseudo-stereo synthesis at those frequencies significantly

30 above the pole of transfer function B(s), i.e., significantly above 265 Hz. The magnitude of the signal output from gain element 205 will determine the

magnitude of the pseudo-stereo synthesis at DC. Thus, the effect of the
previously described transfer function D(s) is emulated by the addition of
signals at summing elements 204 and 207. The constant D_0 of the emulated
transfer function D(s) is preferably approximately 4.5 and may be set as

5   follows:

$$G_{205} = \frac{D_0 - 1}{B_0}$$

where G_{205} is the gain of variable gain element 205. Where variable gain

10   element 201 is set to unity, the left L' and right R' output signals of the
topology of Figure 12 are related to the left L and right R input signals
according to Equation (11).

Note that in the topology of Figure 12, it is possible to control the gain
at any point along a given signal path and achieve identical results. For typical

15   analog implementations, the inputs of a summing network are usually multiplied
by some gain factor. Thus, there are several ways to ensure that the magnitude
of signals provided to summing elements 204 and 207 from filter 202 are
independently adjustable; so utilizing gain element 205 is only one of such
ways. The stereo enhancement portion of the topology of Figure 12 operates in

20   a manner similar to that of the topology of Figures 2a. Thus, the form and
parameter values for transfer function B(s) and C(s) are preferably as stated
previously.

The topology of Figure 13 operates in a manner nearly identical to that
of Figure 12 with one notable exception. Inverter 229 and summing elements

25   227 and 228 are configured so as to replicate the sum-invariant style topology
of Figure 3b. Thus, other than the function of summing element 227,
components within block 45 of the topology of Figure 13 operate in an identical
manner and perform the same function as those components in block 40 of the
topology of Figure 12.

30   Where it is desired to have distinct enhancement pole time constants for
each of the pseudo-stereo synthesis and stereo signal enhancement functions, the

-24-

topologies of Figures 12 and 13 may be modified by eliminating the signal path passing through gain element 205 and altering filter 202 to have a transfer function C(s)D(s).

The topologies of Figures 12 and 13 may be further simplified, and thus
5   implemented at a reduced cost, by slightly sacrificing the spatial attribute of the pseudo-stereo signal. Such a simplified topology is illustrated in Figure 14, where the role of filters 246, 247 and summing element 248 may be performed in analog implementations by a single op-amp configured as a leaky integrator such as, for instance, op-amp 51 of stereo enhancement system 50 of Figure 4.
10 The left L' and right R' output signals and left L and right R input signals in the topology of Figure 14 are related to one another as expressed by Equation (11), where gain element 241 is set to unity. However, the emulated D(s) transfer function will be of the form:

15          $$D(s) = 1 + B(s)(1 - G_{243})$$

where G_{243}, the gain of gain element 243, must be less than unity. As a result, the range of D_0 is restricted as follows:

20          $$B_0 + 1 \geq D_0 \geq 1$$ (12)

Where G_{243} is zero, D(s) will achieve a maximum bass frequency enhancement. Accordingly, where G_{243} equals unity, there will be no bass frequency enhancement. G_{243} should be chosen such that:
25

          $$G_{243} = \frac{B_0 + 1 - D_0}{B_0}$$

Although different applications may require slightly different parameter
30 values, G_{243} should preferably be zero in order to effect the maximum depth possible which, in turn, implies that D_0 should be approximately 4.125. The

-25-

preferred form and associated parameter values for transfer functions B(s) and C(s) are as stated previously. In a manner similar to that of the topologies of Figures 12 and 13, the signals provided to summing elements 244 and 245 may be independently scaled.

5   Implementing the above described stereo/mono enhancement topologies will, in actual embodiments, require an all-pass filter such as the conventional three-pole all-pass filter 250 illustrated in Figure 15. All-pass filter 15 includes three cascaded single pole all-pass filters 251, 252, 253. Isolating each pole to a separate stage minimizes sensitivity to component variation. Note that the

10   first filter 251 should be designed such that R50 = R51. Filter 251 will have a transfer function H(s) and an associated pole time constant τ:

$$H(s) = \frac{1-s\tau}{1+s\tau} \quad \text{where} \quad \tau = R52 \cdot C40$$

15

Filters 252 and 253 will also operate according to the above described transfer function H(s) where the associated time constants τ are determined in a similar manner.

       In the preferred embodiments of the stereo/mono enhancement system

20   that follow, the individual single pole filters 251-253 should be configured according to well known techniques such that resultant three-pole filter 250 has pole time constants of $46\mu s$, $67\mu s$ and $254\mu s$. It is to be understood that a filter utilizing second or higher order sections may used in order to reduce the number of required op-amps. Further, second order filter sections allow for

25   complex pole conjugate pairs. However, such second or higher order filter sections are more sensitive to component variation.

       The preferred embodiment of the present invention is illustrated in Figure 16. The operation of stereo/mono enhancement system 260 is based upon the topology of Figure 13 and, accordingly, the discussion of the topology

30   of Figure 13 is equally applicable to system 260. Note that with the exception of op-amps 256 of all-pass filter 250, each of the op-amps in system 260 of

Figure 16 operates in an inverting mode for reasons discussed earlier. The left input signal L is inverted by op-amp 270 and associated resistors R60 and R61, while the right input signal R is inverted by op-amp 272 and associated resistors R70 and R71. These two inverted signals are scaled and summed at op-amp 273 to extract the monophonic signal component which is then delayed by all-pass filter 250 to produce a pseudo-stereo signal. When switch SW5 connects the output of filter 250 to line 278, the pseudo-stereo signal is summed with the inverted left input signal L and non-inverted right input signal R at the node common to resistors R62-R64. When switch SW4 connects lines 276 and 277, this sum signal is low-pass filtered by capacitor C50 according to the B(s) transfer function. This filtered signal is summed with the inverted left input signal L and the pseudo-stereo signal (synthesized by filter 250) at op-amp 271 to produce the left output signal L' output. Op-amp 275 subtracts the left output signal L' from the sum of the left L and right R input signals.

Switches SW4 and SW5 allow system 260 to operate in one of three possible modes. If switch SW4 connects line 277 to ground via resistor R65, the stereo enhancement filter, e.g., the B(s) function, is disabled. When switch SW5 connects line 278 to ground, thereby disabling the pseudo-stereo synthesis function of filter 250, e.g., function C(s), system 260 will operate in a bypass mode. In this mode, the left L and right R input signals appear unmodified as left L' and right R' output signals, respectively. If, on the other hand, switch SW4 connects line 277 to line 276, the stereo enhancement filter B(s) is enabled. The operating mode of system 260 will now depend upon the position of switch SW5. If switch SW5 now connects line 278 to ground, thereby disabling the pseudo-stereo synthesis function C(s), system 260 operates in a stereo-only mode. If, however, switch SW5 connects filter 250 to line 278, thereby enabling the pseudo-stereo synthesis function C(s), system 260 operates in a dual stereo/mono mode and will spatially enhance both types of input signals.

As discussed with respect to system 80 of Figure 7, the switching between bypass and stereo/mono enhancement modes via switch SW4 exhibits

-27-

relatively low switching noise due to the low-pass filtering function of capacitor C50. The switching of switch SW5 may cause a discontinuity in the output signals. However, such a discontinuity is tolerable in most applications since the gain of the pseudo-stereo signal on line 278 is fairly low as compared to

5   that of the stereo signals. In applications where such a discontinuity is unacceptable, the discontinuity may be minimized using well known zero-crossing switching techniques, or by replacing switch SW5 with a variable gain element controlled by a switching ramp signal.

The selection of appropriate values for the components contained in

10   system 260 may vary depending on the particular application, the desired operating characteristics, and the types of components used. Note, however, that the following constraints should be met in order to realize the benefits of system 260. First, the resistors associated with summing/inverting op-amps 270, 272 and output op-amp 271 should be chosen such that:

15

$$R60=R61$$
$$R70=R71$$
$$R75=R76=R77=R78$$

20   Next, resistor R69 and capacitor C50 should chosen such that the product of their values is as follows:

$$4\tau_p(2B_0+K_1D_0)=R69{\cdot}C50$$

25   After selecting an appropriate value for resistor R69, the remaining resistor values associated with op-amp 271 are determined as follows:

$$R62=R63=\frac{R69}{2B_0}$$

30

$$R64=\frac{R69}{2K_1D_0}$$

-28-

$$R67 = \frac{R69}{2(2B_0 + K_1 D_0)}$$

$$\frac{R69}{R68} = K_1$$

5                                    $R66 = R69$

The resistors associated with op-amp 273 should satisfy the following
ratios:

10                                   $R72 = R73$

$$\frac{R74}{R72} = \frac{C_0}{K_1}$$

where K_1 should be chosen such that $K_1 \geq 2C_0$. In a preferred embodiment,
15   K_1 is equal to 0.4. As in most multi-stage analog circuits, the gain of a given
signal path can be independently controlled at each stage. As a consequence,
there is always a certain amount of flexibility as to what gain occurs where.
The K_1 coefficient is one such degree of freedom which can be chosen
according to convenience. The above constraint on K_1 is recommended for the
20   sake of dynamic signal range in order prevent the output of op-amp 273 from
saturating with maximum input signals on both input channels.

In another embodiment, a stereo/mono system 280 is disclosed below
and illustrated in Figure 17 which operates in accordance with the topology of
Figure 14. Accordingly, the discussion above with respect to the topology of
25   Figure 14 is equally applicable to stereo/mono system 280, where the left L'
and right R' output signals are related to the left L and right R inputs signals
according to Equation (11). The emulated D(s) transfer function is of the form
previously stated with reference to the topology of Figure 14, where D_0 is fixed
at a maximum value such that:

30

$$D_0 = B_0 + 1$$

The stereo enhancement portion of system 280 is performed by op-amps 293, 294 and their respective associated capacitor C60 and resistors R86-R91, and thus implements the B(s) transfer function in a manner identical to stereo enhancement system 70 of Figure 6. Pseudo-stereo enhancement is combined

5   with stereo enhancement by summing the pseudo-stereo signal with the left input signal L before stereo enhancement is performed, as is discussed below.

Op-amp 290 and associated resistors R80-R81 sum and then scale by one-half the left L and right R inputs signals in order to extract the monophonic component (L+R) of the input source. Note that resistors R80 and R81 should

10   be of equal value. This sum signal is filtered by filter 250 according to the C(s) transfer function to synthesize a pseudo-stereo signal. This pseudo-stereo signal is then summed with the left input signal L by op-amp 292 and associated resistors R82-R85. The gain of left input signal through op-amp 292 is unity, while the gain of the synthesized pseudo-stereo signal through op-amp

15   292 may be adjusted according to the desired depth of the pseudo-stereo effect. Accordingly, values for resistors R82-R85 should be chosen as follows:

$$2C_0 = \frac{R83}{R82} = \frac{R84}{R85}$$

20   System 280 includes two switches SW4 and SW5 which allow system 280 to switch, in a manner identical to that of system 260 of Figure 16, between bypass, stereo-only enhancement, and stereo/mono enhancement modes. Thus, when switch SW5 connects line 295 to ground, the operating mode of system 280 is determined by position of switch SW4. If switch SW4

25   connects lines 296 and 297, system 280 operates in stereo-only mode. If switch SW4 connect lines 296 and 298, system 280 operates in bypass mode. System 280 operates in stereo/mono mode when switch SW4 connects lines 296, 297 and switch SW5 connects line 295 to the output of filter 250. As discussed above in reference to previous embodiments, the values of components

30   contained in system 280 may vary depending upon design, component and performance considerations. However, the following constraints should be

satisfied in order to realize the benefits of the embodiment of Figure 17:

$$R80 = R81$$

5

$$\tau_p = R87 \cdot C60$$

$$B_0 = \frac{R87}{R86}$$

$$R88 = R89$$

10

$$R90 = R91$$

The simpler design and lower implementation cost of system 280 as compared to system 260 is achieved by using both the inverting and non-inverting modes of the op-amps therein. Although utilizing both modes of the op-amps as such may adversely affect sound quality, any such degradation in acoustic quality will be slight and well within the performance requirements of many applications.

The topology of Figure 14 can be implemented in an even simpler design allowing attenuation of the input signals. In accordance with another embodiment of the present invention, a stereo/mono enhancement system 300a is disclosed below and illustrated in Figure 18 which requires only four op-amps. The input signals L and R are scaled by a factor K_2. The selection of an appropriate value of K_2 involves consideration of two factors as will be discussed shortly.

The pseudo-stereo portion of system 300a is formed by op-amps 310 and 311 and their associated resistors R100-R108 and capacitors C70-C71. Op-amp 310 first sums the left L and right R input signals, thereby extracting the monophonic component, and then filters this sum according to a single-pole all-pass filter. Op-amp 311 forms the core of a second order all-pass filter which also divides the sum signal by a factor $1 + K_3$. Although somewhat dependent

upon the pole frequencies, the value of K_3 should generally be close to unity in order to minimize sensitivity to component variation. Op-amps 312 and 313 form the stereo enhancement portion of system 300a and operate in a manner similar to stereo enhancement system 70 of Figure 6. Resistors R109-R113

5   allow D_0 to vary between $B_0 + 1$ and 1. Resistor R119 matches the attenuation of the sum signal path to the rest of the circuit.

System 300a includes two switches SW4 and SW5 which allow system 300a to operate in either bypass, stereo only enhancement, or stereo/mono enhancement mode as previously described with respect to systems 260 and

10   280.

The selection of component values in system 300a is dictated by application requirements and component types. The factors K_2 and K_3 can be selected to minimize the component sensitivity of the second order all-pass filter as well as to adjust the overall signal attenuation level. These two factors are

15   constrained as follows:

$$C_0 = \frac{1}{2(1+K_3)}\left(\frac{1}{K_2}-1\right)$$

In a preferred embodiment, K_2 and K_3 are equal to 0.667 and 0.25,

20   respectively. The component values used in the pseudo-stereo portion should satisfy the following constraints:

$$R100 = R102 = \frac{1}{2}R101$$

25     $$R103 = R104$$

$$\tau_1 = \frac{1}{2}R103 \cdot C70$$

$$R106 \cdot C71 = \frac{2}{K_3}(\tau_2 + \tau_3)$$

30

$$R106 \cdot C72 = \frac{\tau_2 \tau_3 (\tau_2 + \tau_3)}{\left(2 - \dfrac{K_3}{2}\right)\tau_2 \tau_3 + \tau_2^2 + \tau_3^2}$$

$$\frac{R105}{R106} = \frac{K_3}{2}\left[1 - \frac{K_3}{2}\frac{\tau_2 \tau_3}{(\tau_2 + \tau_3)^2}\right]$$

$$\frac{R107}{R108} = K_3$$

Time constants τ_1, τ_2 and τ_3 can be any permutation of recommended time constants for the C(s) function poles. The component values used in the stereo enhancement portion should satisfy the following constraints:

$$\tau_p = R114 \cdot C73$$

$$\frac{R109}{R110} = \frac{1}{K_2} - 1$$

$$\frac{R114}{R111} = (B_0 + 1 - D_0)(1 - K_2)$$

$$\frac{R114}{R112} = K_2 B_0$$

$$\frac{R114}{R113} = (D_0 - 1)(1 - K_2)$$

$$R115 = R116$$

$$R117 = R118$$

$$\frac{R117}{R119} = 2\left(\frac{1}{K_2} - 1\right)$$

Resistors R110-R113 provide more flexibility than may be needed for a given set of parameters. For instance, if a maximum value of D_0 is desired, then R111 should be omitted. If, on the other hand, D_0 is desired to equal 1, then R113 should be omitted. The complete set is shown for the sake of

5   generality. It should be noted that the system 300a attenuates the input signals in all modes of operation, including bypass. Thus, the sum of output signals L' and R' will be the sum of input signals L and R multiplied by some constant factor.

It should be noted that most of the systems and topologies described

10   above may be modified to have a gain other than unity by ensuring that the L and R signal paths have an equivalent attenuation or gain. Such modifications will become apparent to those skilled in the art after reading this disclosure.

System 300a of Figure 18 may be modified to have no signal attenuation by slightly compromising the stereo enhancement transfer function B(s). The

15   resultant structure, embodied as stereo/mono enhancement system 300b, is illustrated in Figure 19. System 300b is identical to and operates in the same manner as system 300a of Figure 18 except for the deletion of resistor R119 and the addition of resistors R120-R121. In order to ensure unity gain in bypass mode and no attenuation in the stereo only and stereo/mono

20   enhancement modes, the following constraint should be met:

$$\frac{R109}{R110} = \frac{R120}{R121}$$

System 300b will operate according to a modified enhancement transfer

25   function B'(s) which from the previously defined B(s) transfer function as follows:

$$B'(s) = B(s) + \frac{\dfrac{1}{R111} + \dfrac{1}{R112} + \dfrac{1}{R113}}{\dfrac{1}{R120} + \dfrac{1}{R121}} = B(s) + K_4$$

30

where K_4 is of a value such that:

-34-

$$K_4\left(\frac{1}{R120}+\frac{1}{R121}\right)=\frac{1}{R111}+\frac{1}{R112}+\frac{1}{R113}$$

Although it is desirable for the error factor K_4 to be as small as possible, minimizing K_4 must be balanced with practicality of either maximizing resistors R111-R113 or minimizing resistors R120-R121. Applicant has found that a value of 0.1 for K_4 is fairly easily realized and produces a sound quality virtually indistinguishable from systems operating without such an error factor. This result may be objectively verified by considering that the error factor K_4 comprises a significant portion of the B'(s) transfer function only at higher frequencies and, even then, constitutes only a small fraction of the output signal power.

All of the above described stereo/mono systems may be mapped into the discrete-time digital signal processing domain using the bilinear transform mentioned earlier. A digital implementation is quite useful to allow a user to dynamically adjust parameter values. By way of example, the topology of Figure 12 may be digitally implemented as follows. Figure 20 illustrates a complete data flow diagram for a DSP implementation based upon the topology of Figure 12. Block 320 forms a three-stage all-pass filter, which is equivalent to the C(s) transfer function normalized to a unity magnitude gain. Block 321 performs the B(s) transfer function. Multiplier factor g_5 accounts for the factor C_0 which is not present in the all-pass filter block 320. Similarly, multiplier factor g_4 is scaled by C_0. Note that gain multiplications can be rearranged in the signal flow without affecting functionality. In the preferred implementation the multiplier factors should be chosen as follows:

$$g_1 = -0.991495$$
$$g_2 = 0.894378$$
$$g_3 = -0.392830$$
$$g_4 = 1.440000$$
$$g_5 = 0.200000$$

$$g_6 = 0.057956$$
$$g_7 = 0.962908$$

This implementation thus requires only seven multiplier coefficients and
only five delay storage elements. Note that the architecture of the particular
DSP used may require modifications to the signal flow diagram of Figure 20.
For instance, if the DSP uses fixed-point arithmetic with a small word size,
scaling might be required to avoid saturation at nodes such as those at the
output of block 321 and the output of adder 322. In architectures in which
multiply-accumulate operations are as economical to implement as are simple
addition or multiplication, it may be advantageous to rearrange the
multiplication operations so as to pair with addition operations. Such issues, as
well as the DSP implementation of specific embodiments of the present
invention, are well understood in the art.

While particular embodiments of the present invention have been shown
and described, it will be obvious to those skilled in the art that changes and
modifications may be made without departing from this invention in its broader
aspects and, therefore, the appended claims are to encompass within their scope
all such changes and modifications as fall within the true spirit and scope of this
invention.

CLAIMS

What is claimed is:

1.   A system for enhancing an acoustic image comprising first and second input channels, said system comprising:

5   means for processing said first and second input channels to produce a first output channel; and

means for combining said first output channel and said first and second input channels to produce a second output channel, where said first and second output channels are indicative of a spatially enhanced signal.

10

2.   The system of Claim 1 wherein the means for combining comprises a summing circuit, said summing circuit subtracting said first output channel from a sum of said first and second input channels to produce said second output channel.

15

3.   The system of Claim 1 wherein the means for combining comprises a summing circuit, said summing circuit summing said first output channel with inverted first and second input channels, respectively, to produce said second output channel.

20

4.   The system of Claim 2 wherein the means for processing comprises an integrator.

5.   The system of Claim 4 wherein said integrator comprises:

25   a first op-amp having first and second input terminals and an output terminal, said first input terminal of said first op-amp coupled to receive said first input channel, said second input terminal of said first op-amp coupled to receive said second input channel, said output terminal of said first op-amp providing said first output channel; and

30   a feedback network coupled between said output terminal and second input terminal of said first op-amp.

-37-

6.   The system of Claim 5, wherein said summing circuit comprisesa second op-amp having first and second input terminals and an output terminal, said first input terminal of said second op-amp coupled to receive said first and second input channels, said second input terminal of said second op-amp

5   coupled to receive said first output channel, said output terminal of said second op-amp providing said second output channel.

7.   The system of Claim 1 wherein said means for processing further comprises:

10   means for summing said first and second input channels to produce a sum signal;

        means for phase-shifting said sum signal using an all-pass filter to produce an enhanced sum signal;

        means for combining said enhanced sum signal with said first input

15   channel to produce an intermediate signal; and

        means for filtering said intermediate signal using a low-pass filter to produce said first output channel.

8.   The system of Claim 7 wherein said means for summing and said

20   means for phase-shifting comprise:

        a first op-amp having non-inverting and inverting terminals each coupled to receive said first and second input channels and having an output terminal; and

        a second op-amp having non-inverting and inverting terminals coupled to

25   said output terminal of said first op-amp, said second op-amp providing said enhanced sum signal at an output terminal thereof.

9.   The system of Claim 8 wherein said means for combining said enhanced sum signal with said first input channel comprises a third op-amp

30   having a non-inverting terminal coupled to receive said first input channel and said enhanced sum signal and having an inverting terminal coupled to receive

said second input channel, said third op-amp providing said first output channel at an output terminal thereof.

10.   The system of Claim 9 wherein said means for combining said
5   first output channel and said first and second input channels comprises a fourth op-amp having a non-inverting terminal coupled to receive said first and second input channels and having an inverting terminal coupled to receive said first output channel, said fourth op-amp providing said second output channel at an output terminal thereof.
10

11.   The system of Claim 10 further comprising a first capacitor having a first plate coupled to said non-inverting terminal of said first op-amp and having a second plate coupled to a first node, said first capacitor facilitating a first order all-pass filter.
15

12.   The system of Claim 10 further comprising a feedback network coupled between said inverting terminal and said output terminal of said second op-amp, said feedback network implementing an all-pass filter.

20   13.   The system of Claim 12 wherein said feedback network implements a second order all-pass filter.

14.   The system of Claim 12 wherein said feedback network further comprises:
25   a resistor having a first end coupled to said non-inverting terminal of   ;
said second op-amp;
a first capacitor having a first plate coupled to said first end of said resistor; and
a second capacitor having a first plate coupled to a second plate of said
30   first capacitor and having a second plate coupled to a second end of said resistor and to said output terminal of said second op-amp.

15.   The system of Claim 10 further comprising a feedback network comprising:

a first resistor coupled between said second input and said output terminals of said third op-amp; and

5   a capacitor coupled in parallel with said first resistor.

16.   The system of Claim 1 wherein said means for processing further comprises:

means for summing said first and second input channels to produce a
10   sum signal;

means for phase-shifting said sum signal to produce an enhanced sum signal; and

means for combining said enhanced sum signal with said first input channel and said second input channel to produce said first output channel.

15

17.   A method for spatially enhancing a two channel input signal which may be either a monophonic signal or a stereophonic signal, said method comprising the steps of:

creating a sum signal from said input signal;
20   phase-shifting said sum signal using an all-pass filter to create an enhanced sum signal;

combining said enhanced sum signal with said input signal to produce an enhanced intermediate signal; and

enhancing said enhanced intermediate signal using a sum-invariant stereo
25   enhancement circuit to produce an enhanced output signal.

18.   The method of Claim 17 wherein said step of combining further comprises combining said enhanced sum signal with said first channel of said input signal to produce said enhanced intermediate signal.

30

19.   The method of Claim 17 wherein said step of combining further

comprises combining said enhanced sum signal with said first channel of said input signal and combining said enhanced sum signal with said second channel of said input signal to produce said enhanced intermediate signal.

5   20.   The method of Claim 19 wherein said enhanced sum signal is summed with said first channel of said input signal and subtracted from said second channel of said input signal to produce said enhanced intermediate signal.

10   21.   The method of Claim 17 further comprising the step of creating a difference signal from said input signal, wherein said enhanced sum signal is combined with said difference signal to produce said enhanced intermediate signal.

15   22.   A method for spatially enhancing a two-channel input signal which may be either a monophonic signal or a stereophonic signal, said method comprising the steps of:

           enhancing said input signal using a sum-invariant stereo enhancement circuit to produce a two-channel stereo-enhanced signal;

20   creating a sum signal from said input signal;

           phase-shifting said sum signal to create an enhanced sum signal; and

           combining said enhanced sum signal with said two-channel stereo-enhanced signal to produce a two-channel output signal.

25   23.   The method of Claim 22 wherein said step of combining further comprises summing said enhanced sum signal with a first channel of said stereo-enhanced signal to produce a first channel of said output signal and subtracting said enhanced sum signal from a second channel of said stereo-enhanced signal to produce a second channel of said output signal.

30

           24.   The method of Claim 22, wherein said step of enhancing further

comprises creating a difference signal from said input signal, said two-channel enhanced stereo signal being created from said difference signal using said sum-invariant stereo enhancement circuit.

5   25.   A method for enhancing an input signal comprising first and second input channels to produce a spatially enhanced output signal comprising first and second output channels, said method comprising the steps of:

        generating a sum signal in response to said first and second input channels;

10   generating a difference signal in response to said first and second input channels;

        enhancing said sum signal using a first filter to produce an enhanced sum signal;

        enhancing said difference signal using a second filter to produce an

15   enhanced difference signal;

        summing said enhanced sum signal and said enhanced difference signal to produce an intermediate signal;

        summing said intermediate signal with said sum signal to produce said first output channel; and

20   subtracting said intermediate signal from said sum signal to produce said second output channel.

        26.   The method of Claim 25 wherein said first filter comprises an all-pass filter.

25

        27.   A method for enhancing an input signal comprising first and second input channels to produce a spatially enhanced output signal comprising first and second output channels, said method comprising the steps of:

        generating a sum signal in response to said first and second input

30   channels;

        generating a difference signal in response to said first and second input

channels;

enhancing said sum signal using a first filter to produce an enhanced sum signal;

summing said enhanced sum signal and said difference signal to produce
5 a first intermediate signal;

enhancing said first intermediate signal using a second filter to produce a second intermediate signal;

summing said second intermediate signal with said sum signal to produce said first output channel; and
10 subtracting said second intermediate signal from said sum signal to produce said second output channel.

28.   The method of Claim 27 wherein said first filter comprises an all-pass filter.
15

Fig. 1a (Prior Art)

Fig. 1b (Prior Art)

Fig. 2a

Fig. 2b

Fig. 3a

Fig. 3b

<u>50</u>

Fig. 4

<u>60a</u>

Fig. 5a

60b

Fig. 5b

Fig. 6

Fig.7

Fig. 8a (Prior Art)

Fig. 8b (Prior Art)

Fig. 9a

Fig. 9b

Fig. 10a

Fig. 10b

Fig. 11a

Fig. 11b

Fig. 12

Fig. 13

Fig. 14

Fig. 15

Fig. 16

Fig. 17

Fig. 18

Fig. 19

Fig. 20

INTERNATIONAL SEARCH REPORT

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6   H04S1/00   H04S5/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6   H04S   H03F   H03H   H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,5 425 106 (KATZ ET AL.) 13 June 1995 see column 2, line 18-33 see column 2, line 64 - column 3, line 26 see column 4, line 6 - column 8, line 44 ---	1-3,5-28
A	US,A,4 910 778 (BARTON) 20 March 1990 see column 1, line 35-64 see column 2, line 26 - column 7, line 25 ---	1-3,5-28
A	GB,A,2 180 727 (SGS MICROELETTRONICA) 1 April 1987 see page 1, line 34-47 see page 1, line 59 - page 4, line 9 ---	1-3,5-8, 11,12, 14-16, 25,27

-/--

[X] Further documents are listed in the continuation of box C.   [X] Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
7 October 1996	2 5. 10. 96

| Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016 | Authorized officer

Zanti, P |

1

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB,A,2 187 068 (MICROBOURNE LIMITED) 26 August 1987 see page 1, line 5-9 see page 1, line 47-73 see page 1, line 89 - page 2, line 38 -----	1-6, 9-11,17, 22

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

Intern   al Application No

PCT/US 96/09240

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US-A-5425106	13-06-95	NONE		
US-A-4910778	20-03-90	NONE		
GB-A-2180727	01-04-87	DE-A-	3630965	19-03-87
		FR-A-	2587163	13-03-87
		US-A-	4782530	01-11-88
GB-A-2187068	26-08-87	NONE		